



PST - 100
(Stand for PRO-650/800)

PRO-1200

PRO-1200 (as Monitor)

NEW

PRO-650

PRO-800

Model designations

Stage-Sound Speaker 80W	PRO-650
black, 8 ohms, with swiveling mounting bracket	
Stage-Sound Speaker 100W	PRO-800
black, 8 ohms, with swiveling mounting bracket	
Accessories:	
Floor Stand , black, for PRO-650/800	PST-100

Model designations

Stage-Sound Speaker 200 W	PRO-1200
black, 8 ohms	
Accessories:	
Floor Stand , black, for PRO-1200	QST-185
Wall Bracket , black, for PRO-1200	QWH-035
Mounting Bracket , black, for PRO-1200	PWB-100

● GENERAL

The Pro Sound Speaker series PRO with high speaking and syllable understanding is also in the best way suitable for the Hifi music performance.

These speakers are universally applicable, as they are made of high-quality components, are of light weight and compact dimensions.

● DESIGN

These active speakers have a high-quality scratch resistant and shockproof plastic housing. The PRO-series speakers are in the best way suitable for fixed installation as well as in the mobile acoustic irradiation sector, because of their light weight and the compact dimensions. A stable screw-on metal grille completes the sturdy design.

PRO-1200: This speaker can be used as a monitor or can be set up vertically. Three threaded inserts are used for mounting. An integrated hand grip on the side increases the transport comfort and easy handling.

● EQUIPMENT

The loudspeaker contains a high quality 6.5", 8" or 12" Bass-speaker and a 25 mm and respectively a 34 mm high quality tweeter.

The outstanding sound is also influenced by the acoustically professionally designed housing. Adapted frequency switches and amplifiers provide a high efficiency and an accurate sound characteristic in the various cabinets.

Accessories PRO-1200



● CONNECTION

The speaker boxes are provided with high-quality Speaker sockets as an input terminal. To loop the signal through the boxes a second parallel switched Speaker socket is available.

● STANDS & BRACKETS

Accessories PRO-650 / PRO-800

A mounting bracket is in the scope of supply for the attachment of the speakers. The speakers can be swivelled around 160° by using this bracket, the speaker can be attached in a vertical or horizontal position. Using an adapter flange (scope of supply PST-100) it is possible to mount the speaker onto the on option available **floor stand PST-100**.

Accessories PRO-1200

The **speaker stand QST-185** is suitable for the speaker PRO-1200 and is individually adjustable in height (109–185 mm).

The on option available **wall bracket QWH-035** and **mounting bracket PWB-100** (impact proof) is suitable for our PRO-1200 as well as for all boxes with a 36 mm Ø stand flange. The bracket is 160° rotatable and approx 15° tiltable.

Technical data	PRO-650	PRO-800	PRO-1200
Load rating	80 W (RMS), 120 W (MAX)	100 W (RMS), 150 W (MAX)	200 W (RMS), 300 W (MAX)
Bass-Speaker	1 x 6.5"	1 x 8"	1 x 12"
Horn / Driver	1 x 25 mm polymer dome tweeter	1 x 25 mm polymer dome tweeter	double-radial-34 mm
SPL 1 W / 1 m	91 dB	93 dB	97 dB
Max. SPL	110 dB	112 dB	120 dB
Frequency range	80 – 20.000 Hz	60 – 20.000 Hz	45 – 20.000 Hz
Impedance	8 ohms	8 ohms	8 ohms
Socket adapters	2 x Speaker	2 x Speaker	2 x Speaker
Dimensions (H x W x D)	370 x 240 x 220 mm	410 x 285 x 250 mm	650 x 420 x 330 mm
Weight, Colour	5.3 kg, black	6.6 kg, black	18.4 kg, black