

Active Sub Mini / Technical datasheet



We have the power

This active subwoofer was specially featured by ML for bending wave transducers and can thus be combined to optimum effect with Novasonar flat-panel loudspeakers. The Active-Sub Mini can be used wherever either technical or visual sophistication is required and is a suitable component in numerous applications.

A & E Specifications

Description:

Active subwoofer with crossover and volume control.

Active 200-mm sub-bass, bass-reflex casing, integrated amplifier with active crossover. Black housing, varnished.

Dimensions: 435 mm x 200 mm x 357 mm

Frequency range: 30 Hz bis 240 Hz
Adjustment range: 40 Hz to 180 Hz

Power handling: 120 W / 8 ohms
Sensitivity: 86 dB (1 W / 1m)

Max. SPL: 108 dB (1 m)

Manufacturer: ML Audio+Carbons
Model: Active Sub Mini

DIMENSIONS (HxWxD)	435 mm x 200 mm x 357 mm
WEIGHT	10,5 kg
FREQUENCY RANGE	30 Hz – 240 Hz
POWER HANDLING	120 watts RMS
SENSITIVITY	86 dB 1 watt / 1 metre
CROSSOVER	40 Hz – 180 Hz
IMPEDANCE	8 ohms

All products subject to technical modification without prior notice. Errors excepted

ML Audio + Carbons GmbH Lautsprechertechnik - Ulmenstraße 15 - D-65428 Rüsselsheim
Tel. +49-(0)700-93735565 or +49-(0)163-5306360 - Fax +49-(0)6131-6030796
E-Mail: info@mllaudio.de - Web: www.mllaudio.de