Novasonar Creative 60 / Technical datasheet Novasonar Creative 60 PN





Example: Elliptical shape

Custom-made shape, colour and surface - according to your requirements on design and function!

You want your flatpanel-loudspeaker to be an element in your concept of interior decoration?

We will manufacture your flatpanel-loudspeaker according to your wishes. You can choose exactly the shape, surface and colour you need to make your interior design just perfect.

DIMENSIONS (HxWxD) Sizes and shapes upon request

WEIGHT Subject to size

FREQUENCY RANGE 100 Hz – 18000 Hz

POWER HANDLING 60 watts RMS (HP 48 dB/oct 150 Hz)

SENSITIVITY 85 dB 1 watt / 1 metre

DISPERSION ANGLE HxV 180° x 180°
IMPEDANCE 4 (16) ohms
CONNECTION standard cable

DESIGN Shapes and surfaces upon request

A & E Specifications

Description:

The loudspeaker system that works on the principle of a bending-wave transducer. It has a flat-panel membrane, which is set into vibration by an exciter that is mounted on the rear.

The Novasonar kreativ as decorative element can be manufactured in any geometrical shape and designed with any of the following surfaces:

Genuine wood veneers or laminates, can be smoothed over, varnished, covered with a thin layer of plaster or wallpaper or have a self-adhesive design for laminations.

The frame has a particularly robust design to reduce the transfer of the membrane vibrations to the surrounding structure. A 100-V transformer and a passive crossover network is also available as an option.

Dimensions: ...mm x ...mm x 40 mm

Frequency Range: 100 Hz –18000 Hz

Dispersion Angle: 180° x 180°

Power Handling: 60 W / 4 (16) ohms Sensitivity: 85 dB (1 W / 1m) Max. SPL: 101 dB (1 m)

Manufacturer: ML Audio+Carbons Model: Novasonar Kreativ 60 (PN)



Example: Elliptical shape